

VERTICAL TMR MIXER WAGONS

PRODUCT CATALOG

Chop, mix, add molasses and deliver cattle feed in minutes.



5 MODELS

268 - 1,148 FT³

FULLY EQUIPPED

WHY TORMEX

FULLY EQUIPPED. READY TO WORK.

Every Tormex vertical mixer leaves the plant with the same complete configuration. No option sheets, no surprises: the equipment below is standard on every model.

STANDARD ON EVERY MODEL

- 

Bidirectional flat discharge conveyor
Delivers feed to either side of the bunk.
- 

Magnet on discharge
Catches tramp metal before it reaches the bunk.
- 

Hydraulic directional control valve
Simple control of discharge from the tractor.
- 

Digi-Star EZ3405 electronic scale
Accurate rations, load after load.
- 

Hydraulic discharge door
Fast, controlled unloading.
- 

Tungsten carbide chopping knives
Hard-wearing edge for long and wet forage.



BUILT FOR THE RANCH

From 70 HP

Designed to run with conventional tractors.

Built heavy

Tub floors from 1/2" to 3/4" steel plate.

Low maintenance

Few moving parts and rugged construction, year after year.

Chops long and wet forage

Handles hay, silage and wet ingredients alike.

THE LINEUP

FIVE MODELS. ONE JOB.

Choose by herd size and batch weight. Every model chops, mixes and delivers the same way.



TV760

Small & mid-size operations

268 ft³
CAPACITY

7,606 lb
MAX. LOAD

70 HP
MIN. POWER



TV1100

Daily heavy use

388 ft³
CAPACITY

10,913 lb
MAX. LOAD

80 HP
MIN. POWER



TV1450

Compact, low profile

512 ft³
CAPACITY

13,558 lb
MAX. LOAD

90 HP
MIN. POWER



TV1750

Mid- to large-size operations

618 ft³
CAPACITY

16,976 lb
MAX. LOAD

90 HP
MIN. POWER



TV3250

Large operations • twin auger

1,148 ft³
CAPACITY

28,058 lb
MAX. LOAD

130 HP
MIN. POWER

SPECIFICATIONS

SIDE BY SIDE.

MODEL	TV760	TV1100	TV1450	TV1750	TV3250
Capacity	268 ft ³ 7.6 m ³	388 ft ³ 11 m ³	512 ft ³ 14.5 m ³	618 ft ³ 17.5 m ³	1,148 ft ³ 32.5 m ³
Max. recommended load	7,606 lb 3,450 kg	10,913 lb 4,950 kg	13,558 lb 6,150 kg	16,976 lb 7,700 kg	28,058 lb 12,727 kg
Min. tractor power	70 HP	80 HP	90 HP	90 HP	130 HP
PTO speed	540 RPM	540 RPM	540 RPM	540 RPM*	1000 RPM
Augers	1	1	1	1	2
2-speed gearbox	—	—	—	Standard	Standard
Overall height	8' 4" 2.54 m	8' 5" 2.56 m	9' 2" 2.80 m	9' 10" 3.00 m	9' 10" 3.00 m
Overall width (w/ deflector)	8' 4" 2.54 m	9' 7" 2.92 m	9' 7" 2.92 m	9' 7" 2.92 m	9' 7" 2.92 m
Overall length	16' 5" 5.00 m	17' 7" 5.36 m	18' 2" 5.54 m	18' 4" 5.60 m	28' 0" 8.54 m
Discharge height	2' 6" 0.75 m	2' 6" 0.75 m	2' 0" 0.60 m	2' 0" 0.60 m	2' 0" 0.60 m
Tub floor plate	1/2"	1/2"	3/4"	3/4"	3/4"
Tub wall plate	1/4"	1/4"	1/4"	1/4"	1/4"
Auger flighting	1/2"	1/2"	5/8"	5/8"	5/8"
Tires (x4)	750 / R16	750 / R16	255/70 - R22.5	255/70 - R22.5	255/70 - R22.5
Hub / spindle	8-bolt · 3"	8-bolt · 3"	10-bolt · 4"	10-bolt · 4"	10-bolt · 6"
Stainless steel liner	On request	On request	On request	On request	Standard

* TV1750 also available with a 1000 RPM PTO. Specifications may change without prior notice.

SUPPORT

BACKED BY TORMEX.

Tormex designs and builds its mixers in Torreón, Mexico, and stands behind every unit in the field.

12-MONTH WARRANTY

Against manufacturing defects. Does not cover impact damage, misuse or wear parts.

PARTS IN STOCK

Tormex keeps its critical parts in stock. Most other parts are generic and available from local suppliers.

CUSTOMIZATION ON REQUEST

Stainless steel liner for TV760–TV1750, other Digi-Star scale models, 1000 RPM PTO on the TV1750 and more.



WHICH MODEL FITS YOUR OPERATION?

Tell us your herd size, ration and tractor. We will recommend the right model and send you a quote.

info@tormex.com.mx
+52 (871) 729 2205



LET'S TALK

REQUEST A QUOTE.

Contact Tormex for pricing, availability and your nearest dealer.

PHONE

+52 (871) 729 2205

WEB

www.tormex.com.mx

EMAIL

info@tormex.com.mx

PLANT

C. San Pablo #100 Int. B, Desarrollo Ind. Mieleras,
Torreón, Coahuila, Mexico 27400

